

PVDC Coated Matt BOPP Film (SD-B1MP0)

DESCRIPTION:

SD-B1MP0 grade is biaxially Oriented Polypropylene Matt film coated one side with an aqueous dispersion of polyvinylidene designed for flexible packaging applications.

CHARACTERISTICS:

- ◆ Excellent oxygen barrier, outstanding flavor and aroma barrier
- ◆ Excellent heat resistance, the best mechanical strength
- ◆ Outstanding properties of printable
- ◆ Matte performance

TECHNICAL DATA:

TECHNICAL DATA

Properties	Test	Unit	Typical Value	
PHYSICAL				
Thickness	SD Test	Micron(mil)	21(0.83)	
Yield	SD Test	m ² /kg(in ² /lb)	53.76(37797)	
Unit Weight	SD Test	g/m ² (lb/ream)	18.6(11.41)	
OPTICAL				
Haze	ASTM D1003	%	/	
MECHANICAL				
Tensile strength	MD	ASTM D882	Mpa(Kpsi)	125(18.13)
	TD			275(39.88)
Elongation at break	MD	ASTM D882	%	145
	TD			35
C.O.F. (PVDC/PVDC)	ASTM D1894	/	0.4	
THERMAL				
Heat Resistance	MD	ASTM D1204	%	1.50
	TD			1.0
Seal Strength	ASTM F 88 135℃,0.25MPa,0.5sec		N/15mm(g/in)	1.0(173)
SURFACE				
Surface tension (PVDC side)	ASTM D2578	Dynes/cm	42	
BARRIER				
WVTR-38℃,90%RH	ASTM F1249	g/m ² /24h (g/100in ² /24h)	4.5(0.29)	
OTR-23℃,0%RH	ASTM D3985	cm ³ /m ² · 24h (cc/100in ² · 24h)	9.0(0.58)	

Note: The stated values are typical data and are not specification of guarantee. SD Pack suggest that purchaser confirm product compatibility prior to use of this product. Stated values are believed to be accurate, but all information is presented without guarantee or responsibility on the part of SD Pack CO., LTD.



Shanghai Saidian Packing Materials Co., Ltd.

Head Office: No.190 Meihe Road, Qingpu Dist., Shanghai, PRC

Tel: +86 21 51601858 Fax: +86 21 51567115

Web site: [http:// www.sdianpack.com](http://www.sdianpack.com)

E-mail: sales@sdianpack.com